


ECE 480

***Six Sigma Overview &
Introduction to
Design for Six Sigma***



Six Sigma Companies

3M	ADT Security	Air Products
Allied Signal	American Standard	Americhem
Armstrong	Armstrong World Industries	Asahi Kasai
Astrazeneca	AT&T	Avery Denison
Avnet	Bank of America	BASF
Bayer	BC Hydro	Becton Dickenson
Black & Decker	Boeing	Bombardier
Boston Financial Services	Calloway Golf	Caterpillar
Celanese	City Bank	Chlorox
Conoco	Corning	Cott Beverages
Covenant Health	Crompton	Dannon
Decoma	Degussa	Dell
Delphi	Deutsche Bank	Dow Chemical
Dow Corning	DuPont	Eastman Chemical
Eastman Kodak	Eaton Corp.	Eli Lilly
Emerson	Energizer	Florida Light & Power
Ford	Fortis Health	General Electric
General Motors	Georgia Pacific	Gillette
GlaxoSmithKline	Goodrich	Goodyear
Harley Davidson	HP	Hitachi

More Six Sigma Companies

Honeywell	IBM	Intel
ITT Industries	ITW	John Deere
Johns Manville Corp.	Johnson & Johnson	Kellogg
Kohler Corp.	LG Chemical	Lockheed Martin
Lord	Lubrizol	Maytag
Mckesson	Moog	Motorola
National Semiconductor	NBC News	NCR Corp.
Noranda	Northrop Grumman	Noveon
Omnova Solutions	Owens Corning	Phillips
Pitney Bowes	PPG Industries	Praxair
Raytheon	Rogers Corp.	Rhom & Haas
Royal Bank of Canada	Saint-Gobain	Samsung
SAS Inst.	Scott Seeds	Seagate Technologies
Sherwin Williams	Siemens	Silicon Graphics
Sony	Sprint	Square D
Schlumberger	Sunbeam	Swagelok
Timken	Toyota	Trane
Transfreight	TRW	US Filter
Visteon	WR Grace	Xerox

Six Sigma “Belts”



“Belt”	Responsibilities
Master Black Belt	• Develop and update training materials • Train Black Belts • Mentor and Certify Black Belts
Black Belt	• Execute Projects utilizing Six Sigma • Train Green Belts
Green Belt	• Project Team Members under Black Belt Leadership



Lecture	Six Sigma 'Tour' Lecture Title
 1	WOWing Customers with Six Sigma Products - DFSS
2	Understanding the Customer's Viewpoint - VOC Homework Assignment
3	Quality Function Deployment (QFD) – Customer Driven Development
4	Function Definition & Analysis – Powerful Problem Analysis Technique Homework Assignment
5	Six Sigma Optimization - MAIC


WOWing Customers with Six Sigma Products . . . via Design for Six Sigma



DFSS Discussion Objectives



- Define Quality, Defect, and Sigma Level
- Describe generic DFSS Process flow
- Highlight the DFSS Process with an example
- Explain “What’s different about DFSS” from traditional Engineering Design approach?



Six Sigma is . . .

A Systematic **Data Driven Approach for:**
Continuous Improvement → **MAIC**
Problem Solving → **DFSS**


Quality and Sigma Level Defined



- **“Quality”**: degree of excellence of a Product, Process, Software, IT System, or Service from the *Customer’s Viewpoint*
- **Every process has Variation**. If the performance is too far from target value (beyond a spec. limit), a **Defect** occurs
- **Standard deviation** is a measure of statistical variation (spread) about the mean
- **Sigma Level** of a process is an indication of how often defects are likely to occur

$$\text{Sigma} = \text{Spec. Width} / 2 (\text{Std. Deviation})$$



Matching Product Requirements and Process Capability



Sigma Level	% Out of Spec
6	0.00034
5	0.02327
4	0.62097
3	6.68072
2	30.85375
1	69.14625

Assuming a Long Term
1.5 Sigma Shift

Optimize or Design?



- Voice of Customer
- House of Quality

Identify
CCRs

Identify
Conceptual
Design

Build
Prototype

- Proof-of-Concept
- Bread Board Circuit
- Discrete Components
- Wire Wrap Board

Analyze
Prototype
Perf.

- Collect data
- Statistically Analyze Data
- Design Meet CCRs?

Optimize
Design

- Surface Mount Chips
- Optimized Power
- PC Boards
- Manufacturability
- Robustness

Test &
Validate
Design

- Collect Data
- Statistically Analyze Data
- Run Charts

Package
Design

Document
Design

- Final Report
- Sponsor Docs.

DFSS Process Flow

Define
the
Project


- Charter

- Function Analysis
- Solution Selection Matrix
- Design Proposal

- Survive Use Environment
- Heat Management
- Shock & Vibration

Voice of the Customer and Quality Function Deployment

Identify



Customer Importance

Hows

Customer Needs
Whats

		↑	↓	↓	↑	↓	↓	○
		Thrust	Tot Maint Cost	Mission Fuel Burn	Cycle Life Limits	Weight	Time To Remove	Disk Burst Speed
High Power	3	●						
Low Oper. Cost	4		●	●	△		△	
Meet Range Req'ts	5	△		●		●		
Long Life	2				●			
High Payload	4	●				●		
Easy To Maintain	2						●	
Easy To Troubleshoot	1							
		Lb	\$/Flt Hr	Gal/Flt	Flt Cycles	Lb	Minutes	RPM
		68	36	57	22	41	22	35

System Level Importance

Target Direction

↑ More is better

↓ Less is better

○ Targeted amount

Relationships


● Strong - 9

● Medium - 3

△ Weak - 1


Intense Focus on what the *Customer* wants

Requirements 'Flow Down' from Customer and Design Capabilities 'Flow Up'



System Design

Design



System

Locomotive

Platform

Engine

Generator

Inverter

Traction

Truck

Subsystems


Control

Console

Coupler

Sander

**Requirements
Flow Down**



Assemblies

Parts

- Customers buy **System Performance and Reliability**
- **Design Decisions** are made at **Subsystem, Assembly** and **Parts**
- Systems engineering allows
 - **Flow Down of Customer Requirements** to lower design levels
 - **Rational Design Decisions** to achieve system-level goals

Design for Robust Performance

Optimize


Quantify relationships between CCRs & Design Parameters

- *First principles models*
- *Numerical models (finite elements, lumped parameter, ...)*
- *Designed experiments (DOE)*
- *QFD*

DOE Main Effects Plot



Response Surface



- *Regression to obtain **Transfer Function**:*

$$Y = f(X_1, X_2, X_3) \cong a_0 + a_1X_1 + a_2X_2 + a_3X_3 + a_4X_1X_2 + a_5X_1X_3 + a_6X_2X_3 + \dots$$

$\swarrow \quad \uparrow \quad \searrow$
Main Effects


$\swarrow \quad \uparrow \quad \searrow$
2-Way Interactions

Capture knowledge in Transfer Function libraries & design templates

Statistical vs Deterministic Design:

Switching Power Supply Example

$V_{in} = 85 - 275 \text{ Vac}$




System Requirements:

- V_{in} : 85 - 275 V
- V_O : 5 V, $\pm 5\%$
- 6σ quality
- Low cost

Baseline design

- Isolated switching converter/
feedback section
- Low cost, combine power MOSFET
and control circuit in a 3-pin package



Deterministic Design

Analysis: Transfer function

$$V_o = V_{\text{ref}} + R_2 \left(\frac{V_{\text{ref}}}{R_1} + I_b \right)$$

Choose values for design parameters:

<u>Design Parameter</u>	<u>Value</u>
LM 431I ref voltage, V_{ref} (volts)	2.495
R_1 (ohms)	10000
R_2 (ohms)	10000
Bias current, I_b (amps)	5.0E-06

Substituting: Output voltage = 5.04 volts

**Baseline design meets 5V, +/- 5% performance requirement
But, quality level is not yet determined**

Statistical Design

Analysis: Transfer Function

$$V_o = V_{\text{ref}} + R_2 \left(\frac{V_{\text{ref}}}{R_1} + I_b \right)$$


*Design parameters are statistical. Engineer selects **mean values** and a measure of variability (e.g., **standard deviation**, based on component **tolerance**).*

Design Parameter	Mean	Std Dev	Tolerances	
			Lower	Upper
LM 431I V_{ref} (volts)	2.495	0.0283	0.085	0.085
R_1 (ohms)	10000	33.3333	1%	1%
R_2 (ohms)	10000	33.3333	1%	1%
Bias current, I_b (amps)	5.0E-06	1.15E-06	2.00E-06	2.00E-06

Do a statistical analysis (e.g., Monte Carlo), using Transfer Function and statistical parameter values

Results:

- V_o mean 5.04 volts
- V_o std dev 0.059 volts
- Defects/million 188 (5.06s)



**Baseline design meets 5V, +/- 5% performance
But quality level is only 5σ**

Statistical Design: Approaching “6 σ ”

Design optimization analysis:


- Use Transfer Function to understand response surface shape and output voltage sensitivity to each design parameter
- Reduce defect rate by: (1) shift mean values or (2) reduce design parameter variance

<i>Design Parameter</i>	<i>Mean</i>	<i>Std Dev</i>	<i>Sensitivity</i>
LM 431I V_{ref} (volts)	2.495	0.0283	2
R_1 (ohms)	10000	33.3333	-0.0002495
R_2 (ohms)	10000	33.3333	0.0002545
Bias current, I_b (amps)	5.0E-06	1.15E-06	10000

Design Mod 1: Center distribution by increasing R_1 to 10160 ohms


Results:

- V_o mean 5.00 volts
- V_o std dev 0.058 volts
- Defects/million 20 (5.61s)




Statistical Design: Reaching “6 σ ”

Design Mod 2: Mod 1 plus reduce variance by using 0.1% resistors



Design Mod 3: Mod 2 plus LM 431AI MOSFET to reduce V_{ref} variance



Summary

	<u>Mean</u>	<u>Std Dev</u>	<u>DPMO</u>	<u>Z_{ST}</u>	<u>Cost</u>
Baseline Design	5.04	0.059	189	5.06	100%
Mod 1: Centered via R_1	5.00	0.058	20	5.61	100%
Mod 2: 0.1% Resistors	5.00	0.057	13	5.7	101%
Mod 3: LM 431AI	5.00	0.041	~0	7.58	105%

Statistical design enables prediction of performance, quality and cost during the design process

What's Different About DFSS?

- Disciplined, comprehensive process applicable to all Designs
- “Line of Sight” from Customer Needs to all System Design levels
- Statistical design to understand . . . and reduce Variation
- “New” tools: QFD, Function Analysis, TRIZ, DOE, DFM, statistical tolerance, Robust Design, multi-variable optimizations
- Quality prediction throughout development
- Dedicated Team can develop a Breakthrough Design in months

**But, does not replace need for sound
Engineering Judgment**

Questions & Discussion

